

# REPROLINE 2000 P

## Utilisation

1 Part developer to hard-dot-films of the 4<sup>th</sup> generation.

Line, contact and daylight materials can also be developed. Very hard working in connection with imagesetterfilms with a low fog level and a maximum density. Particularly to be recommended for LED-exposures and FM-scanning. This new generation of developers offers a high constancy at the processing, no "black-spots" and a low tendency to peppercorn formation at low regeneration rates. This developer contains additives against oxidation and deposit. The 1 Part powder mixture is vacuum-packed and therefore grants an excellent storage stability.

## Preparation

A bag will be diluted in 19,4 litres of water to get 20 litres ready-to-use developer or regenerator.

We recommend automatic mixers (i.e. **Tetenal Powdermix** or **Variomix II**).

To avoid dust formation the bag will be emptied with the extended end underneath the water surface.

The ready-to-use solution in the replenisher tank has to be used up within 2 weeks.

## Developing conditions

The following developing conditions will be recommended:

Developer Temperature °C	32	35	38
Developing Time:	s	35	30 25

## Replenishment

The replenishment rate for an average working condition (about 5 m<sup>2</sup>/working day)

Hard-Dot-Films	300 ml/m <sup>2</sup>
Line Films	200 ml/m <sup>2</sup>

## Packaging

### REPROLINE 2000 P

Carton for 4 x 20 litres ready-to-use developer

**Art.-No. 106330**