

# REPRO SUPERFIX SPECIAL

## Utilisation

Universal fixer concentrate for all customary graphic film and paper materials. Suitable for film developing machines and dip tank fixage. Short fixing times, good use with recycling equipment and low smell nuisance are the excellent properties of the concentrate.

## Preparation

### Line Films:

Dilution: 1 + 3

30 litres water + 10 litres concentrate get 40 litres ready-to-use fixing bath or regenerator.

### Imagetter Films:

Dilution: 1 + 3

30 litres water + 10 litres concentrate get 40 litres ready-to-use fixing bath or regenerator.

The ready-to-use solution in the replenisher tank has to be used up within 4 weeks.

## Fixing conditions

The following fixing conditions will be recommended:

### Fixing bath temperature:

max. 5°C under the developing temperature.

### Fixing time:

According to the material  
25 to 35 seconds.

When using recycling equipment the following has to be observed: The silver contents should not fall below 0.3 g silver per litre at the process of silver recovery. At the silver recovery on the circulation the regeneration rate can be decreases about 70%. At the discontinued silver recovery 10-20% of the volume should be exchanged against fresh fixing bath according to each partial silver recovery. The fixing time may extend.

## Replenishment

The replenishment rate amounts: 300 ml/m<sup>2</sup>. The silver contents in the fixing tank should not fall below 6 g silver per litre.

## Packaging

### REPRO SUPERFIX SPECIAL

10 litres concentrate in PE-can

Art.-No. 106326