

# PLATE STAR

## Developer and Replenisher

### Utilisation

Highly buffered, ready-to-use developer for pre-coated positive offset plates. Works self cleaning with a high stability for a very long period of time in machines as well as in dip tanks. Very economical if regenerated with **PLATE STAR replenisher**.

### Usage

	dilution	temperature	developing time	recommended replenishment
machine	undiluted	22 – 24 °C	20 – 30 s	with <b>PLATE STAR replenisher</b> <sup>(1)</sup>
dip tank	undiluted	22 – 24 °C	30 – 50 s	with <b>PLATE STAR replenisher</b> <sup>(2)</sup>
manually	undiluted	20 – 24 °C	---	---

<sup>(1)</sup> Regeneration with **Plate Star replenisher**: according to the type of machine (dip machine: 30 – 50 ml/m<sup>2</sup> / spray machine 50 – 80 ml/m<sup>2</sup>). We recommend to check the solution by measuring aids.

<sup>(2)</sup> Refill manually with undiluted developer until normal first filling level is reached.

### Packaging

#### PLATE STAR developer

10 litres ready-to-use developer  
in PE-can

**Art.-No. 106540**

#### PLATE STAR replenisher

10 litres ready-to-use replenisher  
in PE-can

**Art.-No. 106544**